

## KV-S2025C WorkGroup Color Scanner

The KV-S2025C is a duplex full color desktop scanner that is an ideal scanning system in today's business environment. Compact and lightweight, the KV-S2025C offers a powerful feature set that you would find on more expensive scanners. Equipped with Panasonic Image Enhancement Technology, the KV-S2025C is a versatile binary and color scanner which capture your documents at 24 ppm / 42 ipm in binary, 10 ppm / 18 ipm in color, and up to 600 dpi optical resolution, making your workgroup scanning worries a thing of the past.



- Full Color Duplex Production Scanning at 10 ppm / 18 ipm (Letter, Portrait 150 dpi)
- Panasonic Image Enhancement Technology (PIE)
- PaperPort SE software
- Reliable Throughput Image Viewer – image capture utility included
- R, G, B color drop-out capability
- ISIS® Certified and TWAIN Compliant drivers - standard
- Kofax Certified
- 100 dpi -600 dpi Color / Binary
- SCSI - III

Scanning Face:	Duplex Scanning
Scanning Method:	Front: Three-line (R, G, B) CIS Back: Three-line (R, G, B) CIS
Scanning Speed:	B/W 24 ppm Simplex (Letter, Portrait, 200 dpi) B/W 42 ipm Duplex (Letter, Portrait, 200 dpi) <b>Color 10 ppm Simplex (Letter, Portrait, 150 dpi)</b> <b>Color 18 ipm Duplex (Letter, Portrait, 150 dpi)</b>
Scanning Resolution:	100 dpi -600 dpi Monochrome/Color scanning; Optical resolution
Paper Size:	Business card 2.0" x 2.8" to legal 8.5" x 14" Continuous feed up to 25" (single sheet)
Paper Thickness:	
Single Paper Feed:	2.0 to 5.9 mils (1 mil = 1/1000 inch)
Continuous Paper Feed:	2.36 to 5.9 mils (1 mil = 1/1000 inch)
Paper Weight:	
Single Paper Feed:	10.7 to 33.9 lbs (37.50 to 127.125 g/m <sup>2</sup> )
Continuous Paper Feed:	13.3 to 33.9 lbs (49.875 to 127.125 g/m <sup>2</sup> )
Auto Document Feeder:	100 pages (20 lbs.)
Length Control:	Standard
Image Compression:	Available: Color: JPEG; Monochrome: G3 and G4
Detect Patch Code:	Available through ISIS® driver: Kodak II, III and T
Detect Control Sheet:	Standard
Detect Double Feed:	Standard
External Dimensions:	13.5" W x 11.7" D x 9.4" H
Weight:	18.5 lbs
Power requirement:	AC 100-120V, 50/60Hz
Power Consumption:	Scanning: 1A maximum (scanning); 0.3A (standby), 0.1A (sleep)
Operating environment:	59° to 86° F; 30% TO 80% RH
Storage Environment:	35° to 95° F; 10% TO 80% RH
Accessories:	Installation, & Maintenance Manuals; CD containing Operation, Paper Port software CD, RTIV & P.I.E. Manuals; AC power cable, & Cleaning paper.
Options:	Roller exchange kit (KV-SS0022), Roller Cleaning Kit (KV-SS03), White Roller Kit (KV-SS0023)
Warranty:	One year swap / exchange

[www.panasonic.com/scanners](http://www.panasonic.com/scanners)

Preliminary specifications, all information subject to change without prior notification

For your nearest Dealer/Distributor please call 1-800-742-8086

Technical Support: 1-800-PANASYS (800-726-2797)



**Panasonic**